

▶ Zerust® Axxanol™ Spray-G

For superior corrosion protection in a sprayable grease, use Zerust Axxanol Spray-G. It protects in extreme conditions, such as outdoor storage and overseas shipping.

Axxanol Spray-G provides the protection of a grease in the convenience of a sprayable form. It outperforms many other rust preventative coatings, while being easier to apply and remove, saving time and costs associated with corrosion control. The product has an oily grease consistency and provides advanced corrosion protection for parts and equipment for up to 1 year outdoors and 2 years indoors.

Axxanol Spray-G can be used as a light lubricant while it provides exceptional corrosion protection. The product is resistant to water and is compatible with packaging and most rubber and plastic materials. Test on a small area before use.

Application Example

A large piece of machinery was coated with Axxanol Spray-G before shipment overseas in the open air on deck. The item arrived corrosion-free to the end customer.



▶ Benefits

Sprayable multimetal rust preventative coating

Protects in extreme outdoor conditions

Safe for paint and plastic

Non-hazardous* disposal

Removable with an alkaline cleaner

Application Type

Storage
Shipping
During Operation
May be used with Zerust VCI packaging

*Non-Hazardous Disposal: Product in unopened original container prior to use is non-hazardous waste in the United States according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).



Product comes in an aerosol can and can be used for large and smaller items.

Technical Data

Product Information	Solvent-based corrosion inhibitor spray grease.	
Application	Apply via pressurized spray	
	Application temperature	50 to 90°F (10 to 32°C)
	Coverage	1 lb covers 211 ft ² (20 m ²)
	Layer Thickness	1 mil (25 µm)
	Removability	Alkaline cleaner
	VOC content	< 45%
	Flash Point	≥ 142° F (61° C)
	Viscosity /40°C	> 1123 mm ² /s 40 C
Properties	Indoors	Up to 2 years
	Outdoor	Up to 1 year
	Salt Spray ASTM B-117	1500 Hrs
	Packaging/Hermetically Sealed	Up to 5 years
	Metal types	Multimetal protection
Storage Guidelines	Temp	50 to 90°F (10 to 32°C)
	Duration	Up to 2 years

Availability

Zerust Axxanol Spray-G is sold in a ready to use Aerosol can and in bulk pails and drums.

Part Number	Qty
350-M-00023AC	16 oz
350-M-00023PL	5 Gal
350-M-00023DR	55 Gal

Contact a Zerust Corrosion Expert

Consult a Zerust representative to implement an optimum, cost-effective corrosion prevention system across your production facility and supply chain.

Safety

- Product in unopened original container prior to use does not meet criteria for hazardous waste according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).

Warranty and Disclaimer Information: We guarantee our products conform to documented quality specifications. Product information subject to change without notice. We make no warranty of any kind expressed or implied as to the effects of use (including, but not limited to, damage or injury). For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2015 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor-Tab®, EXCOR®, Flange Saver®, ICT®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, The ZERUST People®, and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

Contact Us

ZERUST® EXCOR®

A product of :
Northern Technologies International Corp



Harita-NTI Limited

A3, First Main Road,
Ambattur Industrial estate,
Ambattur, Chennai - 600058.

Authorised Channel Partner
BARAHI MARKETING PVT. LTD

+91 8449273394
+91 8449273394

info@bmplservices.com

www.bmplservices.com