

### Description

HarKool SS is a moderate duty, semi-synthetic water soluble cutting & grinding fluid. It will increase blade, tool, or wheel life. It is developed with low foaming Emulsifiers & surfactants which offers superior performance while assuring environmental and worker safety. It provides longer sump life due to low oil content.

### Typical Characteristics

Properties	Results	Method
Appearance	Clear Yellow Liquid	Visual
Density @ 29.5°C, g/ml	1.010	ASTM D 1298
pH of 5% in DI Water	9.26	ASTM E70
Mineral oil content	25 to 35	Calculated
5% Emulsion in DI Water	Translucent	Visual

### Features & Benefits

1. Does Not Contain Chlorine, Sulphur, or Phosphorous
2. Provides Longer Sump Life
3. Excellent Tramp Oil Rejection
4. Good Corrosion Protection even at high hardness water level.
5. The product is designed using low foaming emulsifiers & surfactants, hence free from foaming issue
6. No emulsion breakup due to hardness of water
7. Resists microbial growth, hence sump life is high

**Disclaimer:** We cannot anticipate or control the many conditions under which the information and the product may be used. Hence, we make no warranty, express or implied, as to the effects of use (including but not limited to damage or injury) or the results to be obtained, whether or not used in accordance with the directions. The information furnished is believed to be accurate to the best of our knowledge. Harita-NTI is not liable for any loss, damage, incidental or consequential. Buyer assumes all responsibility in use, storage and handling of this product.

## Application

Application	Steel	Stainless steel	Cast Iron
Drilling	✓	✓	✓
Milling	✓	✓	✓
Reaming	✓	✓	✓
Boring	✓	✓	✓
Turning	✓	✓	✓
Tapping	✓	✓	✓
Sawing	✓	✓	✓
Grinding	✓	✓	✓

## Operating Conditions

Temperature	Ambient
Concentration	3 to 20%*
pH @ 29.5°C	9.2 to 9.8
Water TDS	0- 800 ppm

\*Vary for different applications

## Solubility

When mixed with water, it forms a translucent emulsion that provides excellent cooling, lubricity and corrosion protection.

## Storage

Store in (34 to 122°F / 1 to 50°C), dry place and away from sunlight in original packaging for up to 1 years from the date of shipment


Safety & Warning: Review Material Safety Data Sheet for appropriate health and safety warnings before use.

Spillage : Flush with water. Clean and dispose of in accordance with federal, state or local regulations.

Contact Us

**ZERUST EXCOR**

A product of :  
Northern Technologies International Corp



**Harita-NTI Limited**  
A3, First Main Road,  
Ambattur Industrial estate,  
Ambattur, Chennai - 600058.

Authorised Channel Partner  
**BARAHI MARKETING PVT. LTD**

+91 8449273394  
+91 9860037201  
info@bmplservices.com  
www.bmplservices.com

**Disclaimer:** We cannot anticipate or control the many conditions under which the information and the product may be used. Hence, we make no warranty, express or implied, as to the effects of use (including but not limited to damage or injury) or the results to be obtained, whether or not used in accordance with the directions. The information furnished is believed to be accurate to the best of our knowledge. Harita-NTI is not liable for any loss, damage, incidental or consequential. Buyer assumes all responsibility in use, storage and handling of this product.